

MS MUCK SPREADER RANGE SPECIFICATIONS & OPTIONAL EQUIPMENT

SCAN THE
CODE TO
FIND OUT
MORE »



	MS-60	MS-75	MS-90	MS-105
Standard Tyre Size	12.5 x 15 - 14 ply	385 - 65 x 22.5	385 - 65 x 22.5	550 - 60 x 22.5
Axle	70mm 6 stud	70mm 6 stud	70mm 6 stud	80mm 8 stud
Brakes	300 x 60	300 x 60	300 x 60	350 x 90
Volume Capacity	6 cu. yds / 4.6 cu. mtrs / 1000 gal	7.5 cu. yds / 5.7 cu. mtrs / 1250 gal	9 cu. yds / 6.9 cu. mtrs / 1500 gal	10.5 cu. yds / 8 cu. mtrs / 1750 gal
Hydraulic Brakes	○	○	○	○
Hydraulic Lid	○	○	○	○
Ends	4mm	4mm	4.5mm	4.5mm
Drum Thickness	6mm	6mm	6mm	6mm
Case Hardened Chain Flails	1/2" / 13mm	1/2" / 13mm	9/16" / 14mm	9/16" / 14mm
Flail Chain - Quantity	28	28	36	40
HP Requirements	55	65	85	95
End Height	73"	81"	82"	82"
Loading Height	51"	58"	59"	62"
Lights	10' x 54"	10' x 57"	12' x 60"	14' x 60"
Body Dimension	○	○	○	○
Basic Spreader Weight	1330 kgs	1680 kgs	2060 kgs	2280 kgs
OPTIONAL EQUIPMENT				
Slurry Bib 8 inch Deep - Galvanized	○ (DF-0.5)	○ (DF-0.5)	○ (DF-0.5)	○ (DF-0.5)
16/70 x 20 Track Tread	○ (DF-0.5)	○ (DF-0.5)	○ (DF-0.5)	○
550 - 60 x 22.5 fitted to 8 stud	○	○ (DF-2)	○ (DF-2)	○
Jack Screw in lieu of Skid	○	○	○	○
LED Tail Lights	○ (DF-0.5)	○ (DF-0.5)	○ (DF-0.5)	○ (DF-0.5)

Scan the QR code above or visit www.marshall-trailers.co.uk for our retail pricing & full range of options.



(Bearing mounting)



(Drain plug)



(PTO stand)



(Vertically opening lid)

Dealer Fit ● Standard ○ Optional ● Not Available

MARSHALL TRAILERS

PRODUCT BROCHURE 2024
PAGE 28