

FT FEED TRAILER RANGE SPECIFICATIONS & OPTIONAL EQUIPMENT

SCAN THE
CODE TO
FIND OUT
MORE »



	FT-15	FT-20
Length	15' x 5' 6"	20' x 5' 6"
Feed Spaces	32	40
Loading Height	62"	62"
Sides	3mm Steel	4mm Steel
Front	5mm Steel	5mm Steel
Axles	6 stud 70mm	6 stud 70mm
Tyres	12.5 x 15 - 14 ply	12.5 x 15 - 14 ply
Unladen Weight	840 kgs	1080 kgs
Retractable Drawbar	○	○
Swinging Removable Taildoor	○	○
OPTIONAL EQUIPMENT		
Jack Screw in lieu of Skid	○ (DF-0.5)	○ (DF-0.5)
Tombstone Sides	○	○
Removable Seating	○ (DF-2)	○ (DF-2)

Full Opening Removable Rear Door - allows feed trailers to be easily cleaned out.

Retractable Drawbar - maximizes number of available feed spaces.

Axles - new 6 stud 70mm beam axles are used on both models in the range.

Construction - tapered sides to allow for easy feeding. Every model also benefits from a fully welded steel construction with 5mm ends and 3mm or 4mm sides. The majority of the fabrication work is also carried out on our robot welders for a consistent, high-quality finish.

Floor - the entire range has 30mm treated pine floors, which allows effluent to escape and can easily be replaced when worn out.



(Model shown: FT-15 front view)



(Model shown: FT-15 tombstone sides)



(Model shown: FT-15 rear view)



(Model shown: FT-20 rear view)

Scan the QR code above or visit www.marshall-trailers.co.uk for our retail pricing & full range of options.

Dealer Fit ● Standard ○ Optional ● Not Available