

VES REAR-DISCHARGE SPREADER RANGE SPECIFICATIONS & OPTIONAL EQUIPMENT

SCAN THE
CODE TO
FIND OUT
MORE »



	VES-1500	VES-2000	VES-2500
Standard Tyre Size	18.4 x 30 - 12 ply	18.4 x 34 - 12 ply	18.4 x 34 - 12 ply
Axle	8 stud 80mm	10 stud 120mm High Speed Commercial	10 stud 120mm High Speed Commercial
Brakes	350 x 90	420 x 180 S Cam	420 x 180 S Cam
LED Lights	○	○	○
Floor Thickness	4mm	4mm	4mm
Side Thickness	4mm	4mm	4mm
Slurry Door (Removable)	○	○	○
Carrying Capacity	9 tons	12 tons	14 tons
Volume	1427 gal / 6490 ltr / 229 cu.ft	2000 gal / 9120 ltr / 291 cu.ft	2500 gal / 11400 ltr / 363 cu.ft
HP Requirement	80 HP min	100 HP min	135 HP min
Body Dimensions	9' 10" x 5' x 4' 8" Deep	12' 6" x 5' x 4' 8" Deep	15' 7" x 5' x 4' 8" Deep
Loading Height	7' 2"	7' 7"	7' 7"
Unladen Weight	4080 kgs	4380 kgs	5000 kgs
Discharge Rate	5 min. max.	7 min. max.	9 min. max.
Material Feed	Hydraulic Ram	Hydraulic Ram	Hydraulic Ram
Rotor Speed	350rpm	350rpm	350rpm
Spread Width	Up to 16m	Up to 16m	Up to 16m
Standard PTO Input Speed	1000	1000	1000
Tips - Quantity	58	58	58
Overall Width - Standard Wheels	8' 10"	8' 10"	8' 10"
Overall Width - Oversized Wheels	9' 7"	9' 7"	9' 7"
Overall Length	19' 2"	22' 10"	26'
Beater Protection Shear Bolt	10mm Standard	10mm Standard	10mm Standard
Main Ram Oil Volume Maximum	15 litres	20 litres	37 litres
OPTIONAL EQUIPMENT			
23.1 x 26 - 14 ply Tyres	○ (DF-1)	○ (DF-1)	○ (DF-1)
Wide Angle Shaft	○ (DF-0.25)	○ (DF-0.25)	○ (DF-0.25)
Hydraulic Light Covers	○ (DF-2)	○ (DF-2)	○ (DF-2)
LED Beacon	○ (DF-0.25)	○ (DF-0.25)	○ (DF-0.25)
Air Brakes	○	○	○

Scan the QR code above or visit www.marshall-trailers.co.uk for our retail pricing & full range of options.

U.K. & Ireland Patent Numbers - GB2372932 & GB2399267B



(Model shown: VES-1500 front view)



(Model shown: VES-1500 rear view)



(Rear rotor bearings)



(Front upstand)

Dealer Fit ● Standard ○ Optional ● Not Available